

**BRC 50/70 W Bp**

Battery-powered walk behind carpet cleaning machine for deep- and interim cleaning. Economical use on Areas between 600 and 2000 m<sup>2</sup>.

**Standard accessories:**

- Direction of operation forwards
- iCapsol mode
- iCapsol tank on-board
- No. of rollers 2 piece

**Order no.: 1.008-610.0**

**Technical data**

Area performance (Deep cleaning/interim cleaning "iCapsol") (m <sup>2</sup> /h)	450-1250
Air flow rate dm <sup>3</sup> /s	71
Vacuum (mbar/kPa)	184/18
Spray pressure, interim cleaning (bar)	7
Spray pressure, deep cleaning (bar)	7
Spray rate, interim cleaning (l/min)	0.9
Spray rate, deep cleaning (l/min)	4
Working width, brush (mm)	508
Working width, vacuum (mm)	610
Tank fresh/dirt water (l)	76/61
Power rating fan (W)	375
Power rating brush (W)	375
Weight (kg)	172
Dimensions (L x W x H) (mm)	1400x700x1100

## Details

### Description

The BRC 50/70 W Bp is the optimal machine for medium to big size carpet areas. Due to its traction drive the machine can be used effectively for a fast interim as well as deep cleaning in bigger objects. 2 separate detergent tanks enable an automatic detergent metering in the I-Capsol as well as spray- ex mode. The BRC 50/70 W Bp offers an area performance between 450 and 1.250 m<sup>2</sup>.

---

### Application

The BRC 50/70 W Bp is especially suitable for contract cleaner, own-cleaner in hotels and sales rooms as well as congress centres, casinos and for public principles. Mainly to be used for bigger objects with carpet areas up to 2000 m<sup>2</sup>.

---

### Features & Benefits

I-capsol Interim cleaning: Only 20 minutes after cleaning the carpet is dry and re-accessible. I-capsol interim-cleaning extends the time of resoiling. Easy control concept: Clearly arranged operational controls and easy learnable functionalities. Very maneuverable: Due to low profile and compact design also cleaning on smaller areas is no problem. DOSE System with two detergent tanks: For comfortable use and metering of detergent and easy switch between cleaning modes. More flexibility. Economical use of detergent. 73 l water tank volume: For long working hours without interruption for refilling. Big waste water tank opening with transparent lid: Easy to clean and steady control over suction power. Dirt water tank with floating contractor: For longer turbine life-time. Two 50 cm, contrarotating brushes: Distributes the detergent evenly into the carpet fiber and ensures fiber-deep cleaning. In the front adapted, floating brush system: For constant ground contact, also on uneven surfaces and effective cleaning also into the edges without any manual adaption by the machine operator. Automatic brush-/ and water stop when releasing the control lever: For surface protection. Battery powered: Flexible, cable-free and therefore much more economical cleaning. Fast brush change without tools. Optional accessory: Hand- and floor tool for spot cleaning use.

---

## Accessories

### Floor tools

#### Floor tool ID 38,330 mm,1-14bar

3 nozzles, long version, high pressure 1-14 bar

Order no. 4.130-061.0



### Hand tools

#### Hand tool

For cleaning upholstery with puzzi 400/ E and 400 K, with water flow reducer 3.637-029 (except puzzi 440 K)

Order no. 4.130-163.0



### Rechargeable batteries + chargers

#### Charger

Charger for battery 6.654-141 - 12 V. -105 Ah (CV 85/2 RS Bp)

Order no. 6.654-229.0



#### Battery (12 V, 100 Ah)

Use for CV 85/2 RS Bp, 3 pieces needed/ unit - maintenance-free

Order no. 6.654-141.0



## Spray-extraction hoses

### Complete, metal coupling

Complete, metal coupling

Order no. 4.440-644.0



## Teppichreinigungsautomat

### Adapter

For hand tool 4.130-163.0

Order no. 8.631-030.0



### Brush, 500 mm

Standard. For all carpets. 2 required.

Order no. 8.623-068.0



## Vacuum sweepers and scrubber driers - 12V

### Battery (12 V, 100 Ah) (C5) maintenance-free

Order no. 6.654-141.0



### Battery

3 pcs required

Order no. 6.654-141.0



Carpet cleaners

# BRC 50/70 W Bp



---

## Vacuum sweepers and scrubber-dryers - 36 V

### Charger

For battery 3 x 6.654-141.0

Order no. 6.654-229.0

