

Cold water compact class

HD 6/15 C *EU



Cold-water pressure washer for daily commercial use. With its compact dimensions, robust construction and greatest possible manoeuvrability, this unit is a credit to the compact class.

Standard accessories:

- Trigger gun : Easy Press
- Trigger gun with soft grip
- High-pressure hose 10 m
- Spray lance 850 mm
- Triple nozzle (0°/25°/40°)
- Anti-twist system (AVS)
- Pressure switch control



Order no.: 1.150-601.0

Technical data

Power supply (Ph /V /Hz)	1/230/50
Water flow rate (l/h)	230-560
Operating pressure (bar/MPa)	30-150/3-15
Max. pressure bar	190
Max. water feed temperature (°C)	up to 60
Connected load	3.1
Weight (kg)	23
Dimensions (L x W x H) (mm)	360x375x925

Details

Description

This cold-water pressure washer with alternating current drive unit is the ideal entry-level model for commercial end users. The upright HD 6/15 C boasts impressive mobility, compactness and a height-adjustable shaped aluminium push handle. The advantage of the push handle is that it can easily be adjusted to the operator's body height without using tools. In the extended position, the unit's generous stowage facilities ensure that accessories are always ready to hand and put away safely. In the retracted position, this handy unit can easily be stowed in any estate car or service vehicle. It boasts familiar Kärcher features such as a full shock-resistant plastic covering that protects the high-pressure pump from damage and soiling. Other very good features are a power cord storage (with plug lock) and a nozzle compartment arranged practically on the back of the unit. The cleaner comes with a three-way nozzle that enables the water jet to be adjusted quickly and easily. You can choose between a high-pressure pencil jet, a high-pressure fan jet (25°) and a low-pressure fan jet. The low-pressure fan jet (40°) is used for dispensing cleaning agent. The cleaning agent metering valve enables cleaning agent to be mixed continuously with the high-pressure jet. The large-volume oil container, which is very important for ensuring that the unit is always adequately lubricated, can be checked very easily from outside through an oil level inspection glass. The three-piston axial pump with chromed stainless steel pistons and a brass cylinder head guarantees a long service life and low susceptibility to faults. The special feature of this newly developed pump is that both the water inlet and the high-pressure outlet are made of brass, which makes them highly resistant to fracture and corrosion.

Application

Suitable for use in many fields: crafts, trades, cleaning companies, local authorities

Features & Benefits

Adjustable push handle In standard position safe fixing of standard accessories and easy transport possible. Low position for easy transport in different types of transport cars. Brass cylinder head High grade materials for a long service life Easy Press trigger gun reduces holding and operating effort Pressure switch Automatic switch-off of electric motor when gun is closed, energy is saved Three-piston axial pump with stainless steel pistons, swash-plate drive system Direct drive with minimum of moving parts, optimum efficiency, long service life Infinitely variable pressure and water flow control on the unit

Accessories

Adapter for variable pressure spray lance

Adapter for variable pressure spray lance

For items 4.760-230 and 4.760-362 for mounting accessories to lance, M 24/18 x 1.5

Order no. 4.762-075.0



Angular spray lance

Bathroom and eaves gitter spray lance

With nozzle. Specially shaped for cleaning of eaves gutters and for hygienically cleaning WCs. Stainless steel.

Order no. 4.760-073.0



Automatic, self-winding hose reels

Hose drum, automatic, 20 m, coated

Hose reel, automatic, 20 m, coated

Order no. 2.639-919.0



Swivel holder

ABS swivel holder for 2.639-919.0

Order no. 2.639-931.0



Self-winding hose reel with swivel holder, stainless steel, 20 m

Automatic hose reel with swivel holder (high-grade steel)

Order no. 6.391-421.0



Automatic, self-winding hose reels

ABS hose reel stainless steel

High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprung drive. Connection for HP hoses with nipple.

Order no. 2.641-866.0



ABS wall fastening stainless steel

Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.

Order no. 2.641-867.0



Backflow check valve

Backflow preventer

To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection

Order no. 2.641-374.0



Becher-Schaumlanze

Foam lance

Short and handy foam lance with a 1-litre detergent tank directly at the lance. Due to its compact construction it is perfectly suited for foam cleaning of vehicles. Infinitely detergent dosage, swivel connection M22x1,5, adjustable jet angle.

Order no. 6.394-668.0



Tank 1L

Order no. 6.414-954.0



Boron carbide nozzle

Boron carbide nozzle, for machines as of 1000 l/h

In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

Order no. 6.415-084.0



Connector

Nozzle union / Screw union

For connecting HP nozzle and accessories directly to trigger gun (with nozzle union) – 1 x M 22 x 1.5 / 1 x M 18 x 1.5

Order no. 4.402-022.0



Coupling

Double pipe union

For connecting and extending HP hoses. 2 x M 22 x 1,5 connections, brass with rubber protector

Order no. 4.403-002.0



Dirt Blaster

Dirt Blaster

Dirt blaster - rotating pencil jet - 10x cleaning power. Ceramic nozzle and bearing ring for long service life. max. 180 bar/18 MPa, 60 °C

Order no. 4.767-022.0



Dirt blaster – non-changeover

Dirt blaster - non-changeover

Dirt blaster – rotating pencil jet – 10x cleaning power. Ceramic nozzle and bearing ring for long service life. Max. 300 bar/30 MPa, 85 °C

Order no. 4.763-931.0



Doppelstrahlrohr

Double spray lance 960 mm

Infinitely adjustable control of the working pressure directly on the handle with full water quantity. Suitable above all for agriculture (e.g. cleaning stalls).

Order no. 6.394-665.0



Drum and tank cleaning

ABS barrel cleaner

The BC 14/12 is an spray system for the efficient interior cleaning of containers and barrels, specially oak barrels with a volume of between 225 and 600 litres. One cleaning cycle is completed within 36 seconds and every spot in the container is covered by a water jet. After cleaning is finished the BC 14/12 can easily and conveniently take up the dirty water. The transformer included with the BC 14/12 makes it possible to use it worldwide (110 - 240 V, 50 - 60 Hz). The nozzle kits included make possible use with high-pressure cleaners with a water volume of 600 to 1400 l / h. Electrical components are protected in accordance with IP 55.

Order no. 2.641-740.0



Easy Foam Set

Easy Foam Set with RM injector

HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.

Order no. 2.640-691.0



Easy Press high-pressure gun with holding power reduction (Kärcher patent)

Easy Press high-pressure gun with soft grip insert

Easy Press HP trigger guns, for HP hoses NW 6 / NW 8 with swivel diameter 11 mm

Order no. 4.775-463.0



Fine-mesh water filter

Fine mesh water filter, 80 µm, R 3/4" + 1", with adapter

Mounted to machine inlet, 80 µm, with adapter R 3/4" / 1"

Order no. 4.730-102.0



Flexible spray lance

Jet pipe flexible

Infinitely variable adjustment of the angle of the spray lance from 20° - 140°. Especially suitable for cleaning difficult-to-reach areas such as roof gutters, car roofs, undercarriages or wheel cases.

Order no. 6.394-654.0



Foam nozzle mounting kit

Anbausatz Schaumdüse

For applying foam detergent in metered quantities in sanitary and food areas, or where long reaction time is necessary, mounts to spray lance in place of HP nozzle

Order no. 2.637-926.0



Food industry version

High-pressure hose food DN6 15m

Food industry version, AVS connection in the trigger gun. grey NW 6/155°C/250 bar

Order no. 6.391-654.0



Geka coupling

Geka coupling with hose liner, R 3/4" with hose liner

Order no. 6.388-455.0



Geka coupling with hose liner, R 1/2" with hose liner

Order no. 6.388-461.0



Geka coupling with female thread, R 3/4" with female thread

Order no. 6.388-473.0



Hard surface cleaner FR 30

FR 30 hard surface cleaner

A rotating nozzle beam with Kärcher Power nozzles has an area coverage up to 10 times larger than conventional methods. Ceramic bearings, plastic cover for good manoeuvrability. Machine specific nozzle kit has to be ordered separately. Max. 180 bar / 850 l/h / 60 °C

Order no. 2.641-065.0



Hard surface cleaner FR 30 ME

FR 30 ME hard surface cleaner

A rotating nozzle beam with Kärcher Power nozzles has an area coverage up to 10 times larger than conventional methods. Stainless steel version. Ceramic bearings. Integral vacuum connection. Machine specific nozzle kit has to be ordered separately. Max. 250 bar / 1100 l/h / 80 °C

Order no. 2.640-355.0



HP detergent injector

Detergent injector for high pressure

Cleaning agent dosage at high pressure 3 - 5 %

Order no. 3.637-170.0



Inno Foam Set

Inno Foam Set with RM injector

HP foam system for use with mobile and stationary HD/HDS units for cleaning and disinfection. Twin spray lance with foam nozzle and changeover to HP jet for clear rinsing etc., HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.

Order no. 2.640-151.0



Longlife 400

High pressure hose DN 6, 10 m, Longlife

With patented AVS connection in the trigger gun (pivot-mounted).

Order no. 6.391-882.0



Longlife 400 with unions on both sides

High-pressure hose 1.5 m, DN 8, including connecting parts

with union on both sides, M22 x 1.5 with anti-kink protection. For connecting hose reels with M22 x 1.5 union.

Order no. 6.390-178.0



Longlife food industry version

High-pressure hose Longlife 400, 15 m, DN 6, AVS trigger gun connection

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)

Order no. 6.391-888.0



Machine-specific nozzle kit for HSC##

Nozzle pack for hard surface cleaners (machine-specific) 500 - 650 l/h

Machine-specific nozzle kit Kärcher power nozzle for hard surface cleaners

Order no. 2.640-401.0



Machine-specific nozzle kit with order no. 3.637-170

Machine-specific nozzle kit for order no. 3.637-170 HD 500-700 l/h

For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union

Order no. 4.769-045.0



Nozzle kits for Inno/Easy Foam Set

Nozzle kit 055 for Inno/Easy Set 500 - 600 l/h

Optimal adaptation to different machine outputs for economic use.

Order no. 2.640-870.0



Nozzle pack for wet blasting attachment

Nozzle pack for wet blasting attachment 035

Consisting of wet-blasting nozzle and nozzle insert, only for use with wet-blasting attachment 4762-010/-022

Order no. 2.638-526.0



Nozzle union

Nozzle union

With protector for high-pressure and Power nozzles M 18 x 1.5

Order no. 5.401-210.0



Pipe cleaning hose, ID 6

Pipe cleaning hose, NW 6, 20 m

Especially flexible high-pressure hoses for inner pipe cleaning (thread connection for nozzle R 1/8).

Order no. 6.390-028.0



Pipe cleaning hose, NW 6, 30 m

Especially flexible high-pressure hoses for inner pipe cleaning (thread connection for nozzle R 1/8).

Order no. 6.390-029.0



Pipe cleaning nozzle

Rotating pipe cleaning nozzle

With female thread, different spraying directions for environment-friendly cleaning of blocked drains and pipes. Nozzle orifices are positioned so that the nozzle pulls itself and the hose into the pipe. With R 1/8" connection to the pipe cleaning hose. 4 rotating jets

Order no. 6.415-428.0



Power nozzle spray angle 25°

Power nozzle spray angle 25°

Fan jet nozzle for large-area coverage and stubborn dirt and stains.

Order no. 2.883-803.0



Push-on washing brush

Push-on washing brush

With clamp for mounting directly to units' double or triple nozzle.

Order no. 4.762-328.0



Push-on washing brush, M18 x 1.5

General-purpose cleaning on all surfaces. With clamp for mounting directly to spray lance. Connection M 18 x 1.5.

Order no. 4.762-016.0



Rollover nozzle holder

Rollover nozzle holder

Changes from solid to fan jet with flick of the wrist. Knurled nut for changeover to low pressure detergent intake, without nozzles (order machine-specific Kärcher Power nozzle separately)

Order no. 4.764-012.0



Cold water compact class

HD 6/15 C *EU



Rotary coupling

Rotary coupling

Reliably prevents high-pressure hose twisting. Connection M 22 x 1.5 m. protector

Order no. 4.401-076.0



Rotating coupler

Reliably prevents high-pressure hose twisting. Connection M 22 x 1.5 m. protector

Order no. 4.401-091.0



Rotating spray lances

Jet pipe packaged only for replacement

Order no. 4.760-663.0



Jet pipe packaged only for replacement

Order no. 4.760-664.0



Jet pipe packaged only for replacement

Order no. 4.760-660.0



Rotating spray lances

Jet pipe packaged only for replacement

Order no. 4.760-661.0



Jet pipe packaged only for replacement

Order no. 4.760-662.0



Rotating washing brush

Rotary wash brush

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 80 °C. M 18 x 1.5. (replaceable brush element)

Order no. 4.762-284.0



Rotating washing brush for machines <lt; 800 l/h

Driven by water jet. Gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 80 °C. M 18 x 1.5. (replaceable brush element)

Order no. 4.762-288.0



Spacer (including nozzle union)

Spacer (incl.nozzle union)

Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.

Order no. 5.394-294.0



Special hoses

High-pressure hose, 1.5 m DN 8, connection to hose reel

Order no. 6.388-886.0



Spray lance

Jet pipe packaged only for replacement

Order no. 4.760-667.0



standard

High-pressure hose, 10 m, DN 6, AVS gun connection Ø 11 mm

With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/250 bar

Order no. 6.391-238.0



HD-Schlauch DN 6, 15m

Order no. 6.391-394.0



High-pressure hose, 10 m DN 8, AVS trigger gun connection

With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 8/155°C/315 bar

Order no. 6.390-025.0



standard

High-pressure hose, 15 m DN 8, AVS trigger gun connection

With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 8/155°C/315 bar

Order no. 6.390-185.0



High-pressure hose, 20 m DN 8, AVS trigger gun connection

With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 8/155°C/315 bar

Order no. 6.390-171.0



Starting current limiter

Starting current limiter

Reduces starting current in single-phase supply and protects line fuse.

Order no. 2.637-495.0



Suction filter

Suction filters with non-return valve

With non-return valve, brass

Order no. 4.730-012.0



Suction filter without non-return valve

Without non-return valve, brass

Order no. 4.730-019.0



Suction filter

Water filter

Order no. 6.414-956.0



Teleskopstrahlrohr

Telescopic jet pipe

Order no. 6.394-690.0



Triple nozzle, touchless changeover

Triple nozzle, touchless changeover

Quick and convenient spray jet changeover by swivelling the nozzle. Choose from high-pressure pencil jet, high-pressure fan jet (25°), manual changeover to low pressure fan jet (40°). On machines with injector, the low-pressure fan jet is used for picking up and applying detergent. M18 x 1.5 connection.



Order no. 4.767-001.0

Triple nozzles

Triple jet nozzle 034 nur fuer Ersatz

Order no. 4.767-147.0



Undercarriage spray lance

Underbody lance

Mobile. For effective and convenient cleaning of underbodies, chassis and wheel arches. Stainless steel. Without HP nozzle.

Order no. 4.760-245.0



Variable pressure spray lance

Variable pressure spray lance, 1,040 mm

With integrated pressure gauge for infinitely variable pressure control directly on the spray lance. Nozzle union M 24 x 1.5. Addition of cleaning agent at low pressures.

Order no. 4.760-230.0



Variable pressure spray lance, 670 mm

With integrated pressure gauge for infinitely variable pressure control directly on the spray lance. Nozzle union M 24 x 1.5. Addition of cleaning agent at low pressures.

Order no. 4.760-362.0



Water supply hose

Water supply hose

NW 13 R1" / R 3/4", up to 30 °C

Order no. 4.440-038.0



Water supply hose

NW 19 R1" / R 3/4", up to 85 °C, for pick-up

Order no. 4.440-207.0



Cold water compact class

HD 6/15 C *EU



Wet blasting attachment (without nozzle)

Wet blasting attachment with flow control (without nozzle)

Adds abrasive to high-pressure jet. For removing paint, rust, scaling. Mounts to spray lance instead of the of high-pressure nozzle. With flow control.

Order no. 4.762-010.0



Wet blasting attachment without flow control (without nozzle)

Adds abrasive to high-pressure jet. For removing paint, rust, scaling. Mounts to spray lance instead of the of high-pressure nozzle. Without flow control.

Order no. 4.762-022.0

